



PRO SERIES	FC-7664 PRO-4G	FC-7668 PRO-4G
Picture		
Kit Accessoires Included	1* Wired Keypad	1* Wired Keypad
System Network	TCP/IP+4G Dual Network	TCP/IP+4G +PSTN
Alarm Zones	32 Wireless+8 Wired + 56 RS485 + 32 Power Bus	64 Wireless+16 Wired + 128 RS485 +48 keyboard expansion zones+ 64 Power Bus+192 CAN BUS zones
Dimensions	(WxHxD) 290x240x87 mm	(WxHxD) 290x240x87 mm
Housing Material	ABS Fire-resistant Box	ABS Fire-resistant Box
Wireless Frequency	FSK433MHz/868MHz	FSK433MHz/868MHz
Installation Location	Indoor Use For Wall Mounted	Indoor Use For Wall Mounted
Menu Voice Guidance	Customized	Customized
DHCP Function	Support	Support
Duress Password	Yes	Yes
Entry & Exit Delay	Yes	Yes
Number of Users	32 Users + 1 Admin +1 Main	32 Users + 1 Admin +1 Main
Number of voice phone No.	4	16
Number of wireless remotes	8	8
Number of wired keypad	8(Each keypad support extra 3 wired zones)	16(Each keypad support extra 3 wired zones)
Number of wireless doorbell	1	1
Number of wireless Switch	32CH	32CH
Partitions And Areas	4	8
Number of wireless Siren	4 for dual way siren, multiple f or single way siren	4 for dual way siren, multiple f or single way siren
PGM Outputs	1	3
Event log	1000	1000
Backup Battery Type	12V DC, 7ah lead acid battery	12V DC, 7ah lead acid battery
Max. run time on backup Batte	16 h if connect 1 wired keypad	16 h if connect 1 wired keypad
Max. receiving range	300 m	300 m
Max. sending range (Outdoors)	300 m	300 m
Power Supply Unit	15V/2.5A	15V/3A
GSM Dialing Protocols	Ademco Contact ID	Ademco Contact ID
IP/GPRS CMS protocol	SIA-TCP, SIA-UDP, Meian	SIA-TCP, SIA-UDP, Meian
CMS Platform Docking Way (Central management)	Support 2 CMS Server Address Main Server+Backup Server (Meian Server/SIA-TCP,SIA-	Support 2 CMS Server Address Main Server+Backup Server (Meian Server&SIA-TCP,SIA-
Camera Supported	Support	Support
WEBIE	Support	Support
Packing	4 Sets/Carton	4 Sets/Carton
Certifications	CE,FCC,RoHS	CE,FCC,RoHS